


05/23/00



JCS80 U.S. PTO

00575122-0523700

Please type a plus sign (+) inside this box → ☒

Approved for use through 09/30/2000. OMB 0651-0032  
 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE  
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.	PP17US
First Inventor or Application Identifier	Simon Robert Walmsley
Title	METHOD AND APPARATUS OF IMAGE CONVERSION

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

- ☒ \* Fee Transmittal Form (e.g., PTO/SB/17)  
(Submit an original and a duplicate for fee processing)
- ☒ Specification [Total Pages 23]  
(preferred arrangement set forth below)
  - Descriptive title of the invention
  - Cross References to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to Microfiche Appendix
  - Background of the invention
  - Brief Summary of the invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
- ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 15]
- Oath or Declaration [Total Pages 3]
  - ☒ Newly executed (original or copy)
  - ☐ Copy from a prior application (37 C.F.R. § 1.63(d))  
(for continuation/divisional with Box 16 completed)
    - ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

\* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28)

ADDRESS TO: Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

- ☐ Microfiche Computer Program (Appendix)
- Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - ☐ Computer Readable Copy
  - ☐ Paper Copy (identical to computer copy)
  - ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

- ☒ Assignment Papers (cover sheet & document(s))
- ☐ 37 C.F.R. §3.73(b) Statement of Power of Attorney (when there is an assignee)
- ☐ English Translation Document (if applicable)
- ☐ Information Disclosure Statement (IDS)/PTO-1449
- ☐ Preliminary Amendment
- ☐ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
- ☒ \* Small Entity Statement(s) filed in prior application, (PTO/SB-09-12) Status still proper and desired
- ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
- ☐ Other.

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. \_\_\_\_\_  
 Prior application information: Examiner \_\_\_\_\_ Group / Art Unit: \_\_\_\_\_  
 For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label 24011 or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name	Kia Silverbrook				
	Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	Zip Code	2041
Country	AUSTRALIA	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

Name (Print/Type)	Kia Silverbrook	Registration No. (Attorney/Agent)	
Signature	<i>[Signature]</i>	Date	May 16, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Times will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

**STATEMENT CLAIMING SMALL ENTITY STATUS  
 (37 CFR 1.9(f) & 1.27(c))--SMALL BUSINESS CONCERN**

Docket Number (Optional)  
 PP17US

Applicant, Patentee, or Identifier: Silverbrook Research Pty Ltd  
 Application or Patent No.: \_\_\_\_\_  
 Filed or Issued: May, 2000  
 Title: METHOD AND APPARATUS OF IMAGE CONVERSION

I hereby state that I am  
☒ the owner of the small business concern identified below;  
☐ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN Silverbrook Research Pty. Ltd.

ADDRESS OF SMALL BUSINESS CONCERN 393 Darling Street, Balmain, NSW 2041, Australia

I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.

I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

- ☒ the specification filed herewith with title as listed above.  
☐ the application identified above.  
☐ the patent identified above.

If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

- Each person, concern, or organization having any rights in the invention is listed below:  
☒ no such person, concern, or organization exists.  
☐ each such person, concern, or organization is listed below.

Separate statements are required from each named person/concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss or entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

NAME OF PERSON SIGNING Kia Silverbrook

TITLE OF PERSON IF OTHER THAN OWNER \_\_\_\_\_

ADDRESS OF PERSON SIGNING 393 Darling Street, Balmain, NSW 2041, Australia

SIGNATURE  DATE May 16, 2000

09575122, 052300

## METHOD AND APPARATUS FOR IMAGE CONVERSION

### FIELD OF THE INVENTION

5 The invention relates to a compact printer system able to print full-color, business card size documents from a device about the size of a pen. The system includes various hot-connectable modules that provide a range of functions. In particular the invention relates to a method of, and an apparatus for, image conversion.

10 Reference may be had to co-pending applications claiming priority from Australian Provisional Patent Application number PQ0560 dated 25 May 1999. The co-pending applications describe related modules and methods for implementing the compact printer system. The co-pending applications are as follows:

USSN	Our Docket Number	Our Title
TBA	PP01	Compact Color Printer Module
TBA	PP02	Modular Compact Printer System
TBA	PP03	Nozzle Capping Mechanism
TBA	PP04	Ink Cartridge for Compact Printer System
TBA	PP07	Controller for Printer Module
TBA	PP08	Camera Module for Compact Printer System
TBA	PP09	Image Processor for Camera Module
TBA	PP10	Memory Module for Compact Printer System
TBA	PP11	Effects Module for Compact Printer System
TBA	PP12	Effects Processor for Effects Module
TBA	PP13	Timer Module for Compact Printer System
TBA	PP15	Color Conversion Method for Compact Printer System
TBA	PP16	Method and Apparatus of Dithering

### 15 BACKGROUND OF THE INVENTION

Microelectronic manufacturing techniques have led to the miniaturization of numerous devices. Mobile phones, personal digital assistant devices, and digital cameras are very common examples of the miniaturization trend.

One device that has not seen the advantage of microelectronic manufacturing techniques is the printer. Commercially available printers are large compared to many of the devices they could support. For instance, it is impractical to carry a color printer for the purpose of instantly printing photographs taken with known compact digital cameras.

A compact printhead has been described in co-pending United States Patent Applications filed simultaneously to the present application and hereby incorporated by cross reference:

USSN	Our Docket Number	Our Title
TBA	MJ62	Fluidic seal for an ink jet nozzle assembly
TBA	IJ52	Ink jet printhead having a moving nozzle with an externally arranged actuator
TBA	IJM52	Method of manufacture of an ink jet printhead having a moving nozzle with an externally arranged actuator
TBA	MJ63	Ink jet printhead nozzle array
TBA	MJ58	Nozzle guard for an ink jet printhead

In order to put a compact printer system into practical effect it is necessary to be able to capture an image for printing. An image can be captured by various forms of sensors but a popular sensor is a Bayer color filter array (CFA). The captured image must be processed to a suitable form for printing. Various techniques for processing the Bayer CFA image are known but they suffer from various drawbacks that make an alternative method desirable.

#### SUMMARY OF THE INVENTION

In one form, the invention resides in a method for up-interpolating a Bayer mosaic image from input space to output space, said Bayer mosaic image comprising a plurality of four-pixel blocks, each pixel in said blocks being one of three different colors with two of said pixels being a dominant color and two of said pixels being non-dominant colors, said method including the steps of:

reading a two dimensional color plane of said Bayer image for each said color;

mapping said pixels of said dominant color from said input space to said output space by:

    multiplying each ordinate of said input space by  $1/\sqrt{2}$ ; and  
    scaling coordinates of said input space to a normalized coefficient

5           kernel by multiplying said ordinates by  $1/\sqrt{2}$ ;  
mapping said pixels of said non-dominant colors by multiplying each ordinate of said input space by  $1/2$ ;

for each color, convolving said input space pixels with a coefficient kernel for each color; and

10          writing said mapped pixels to a storage location.

The most common arrangement of a Bayer mosaic image is for the dominant color pixels to be green and the two non-dominant color pixels to be red and blue. However, the Bayer mosaic image need not be limited to this arrangement. In some situations it may be appropriate to optimize the image for the red or blue ends of the spectrum.

15          In a further form the invention resides in an apparatus for up-interpolating a Bayer mosaic image from input space to output space, said Bayer mosaic image comprising a plurality of four-pixel blocks, each pixel in said blocks being one of three different colors with one of two of said pixels being a dominant color and two of said pixels being non-dominant colors, said apparatus comprising:

20           an input buffer for each color for storing said input space pixel values;  
            a coefficient kernel for each color, said coefficient kernel for said dominant color being normalized;  
            a convolve unit for each color for convolving said input space pixel values  
25           with said kernel coefficients; and  
an output buffer for storing mapped pixel values.

Further features of the invention will be evident from the following description.

## 30      BRIEF DESCRIPTION OF THE DRAWINGS

In order to assist with describing preferred embodiments of the invention, reference will be made to the following figures in which:

FIG 1 is a printer module;

FIG 2 is a camera module;

FIG 3 is a memory module;

FIG 4 is a communication module;

FIG 5 is a flash module;

5 FIG 6 is a timer module;

FIG 7 is a laser module;

FIG 8 is an effects module;

FIG 9 is a characters module;

FIG 10 is an adaptor module;

10 FIG 11 is a pen module;

FIG 12 is a dispenser module;

FIG 13 is a first compact printer configuration;

FIG 14 is a second compact printer configuration;

FIG 15 is a third compact printer configuration;

15 FIG 16 is a fourth compact printer configuration;

FIG 17 is a 2G mosaic pattern in a Bayer color filter array (CFA);

FIG 18 shows color plane pixels in relation to full color filter array resolution;

FIG 19 illustrates an image reconstruction and resampling method for the green plane;

FIG 20 shows the calculation of the distance between rotated pixels in the green

20 plane;

FIG 21 shows mapping movement in unrotated CFA space to rotated CFA space.

FIG 22 shows the steps in the resample process; and

FIG 23 is a block schematic diagram of a convolve unit for the resampling process.

## 25 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIGs 1 to 12, there are shown various modules that together form a compact printer system. Individual modules can be attached and detached from the compact printer configuration to allow a user-definable solution to business-card sized printing. Images can also be transferred from one compact printer to another without the use of a secondary computer system. Modules have a minimal user-interface to allow straightforward interaction.

30

A compact printer system configuration consists of a number of compact printer modules connected together. Each compact printer module has a function that contributes to the overall functionality of the particular compact printer configuration.

Each compact printer module is typically shaped like part of a pen, physically connecting with other compact printer modules to form the complete pen-shaped device. The length of the compact printer device depends on the number and type of compact printer modules connected. The functionality of a compact printer configuration depends on the compact printer modules in the given configuration.

The compact printer modules connect both physically and logically. The physical connection allows modules to be connected in any order, and the logical connection is taken care of by the compact printer Serial Bus - a bus that provides power, allows the modules to self configure and provides for the transfer of data.

In terms of physical connection, most compact printer modules consist of a central body, a male connector at one end, and a female connector at the other. Since most modules have both a male and female connector, the modules can typically be connected in any order. Certain modules only have a male or a female connector, but this is determined by the function of the module. Adaptor modules allow these single-connector modules to be connected at either end of a given compact printer configuration.

A four wire physical connection between all the compact printer modules provides the logical connection between them in the form of the compact printer Serial Bus. The compact printer Serial Bus provides power to each module, and provides the means by which data is transferred between modules. Importantly, the compact printer Serial Bus and accompanying protocol provides the means by which the compact printer system auto-configures, reducing the user-interface burden on the end-user.

Compact printer modules can be grouped into three types:

- image processing modules including a Printer Module (FIG 1), a Camera Module (FIG 2), and a Memory Module (FIG 3). Image processing modules are primarily what sets the compact printer system apart from other pen-like devices. Image processing modules capture, print, store or manipulate photographic images;
- housekeeping modules including an Adapter Module (FIG 10), an Effects Module (FIG 8), a Communications Module (FIG 4), and a Timer Module (FIG 6). Housekeeping modules provide services to other modules or extended functionality to other modules; and
- isolated modules including a Pen Module (FIG 11) and a Laser Module (FIG 7). Isolated modules are those that attach to the compact printer system

but are completely independent of any other module. They do not necessarily require power, and may even provide their own power. Isolated Modules are defined because the functionality they provide is typically incorporated into other pen-like devices.

Although housekeeping modules and isolated modules are useful components in a compact printer system, they are extras in a system dedicated to image processing and photographic manipulation. Life size (1:1) illustrations of the compact printer modules are shown in FIGs 1 to 12, and example configurations produced by connecting various modules together are shown in FIGs 13 to 16.

FIG 1 shows a printer module that incorporates a compact printhead described in co-pending United States Patent Applications listed in the Background section of this application, incorporated herewith by reference, and referred to herewith as a Memjet printhead. The Memjet printhead is a drop-on-demand 1600 dpi inkjet printer that produces bi-level dots in up to 4 colors to produce a printed page of a particular width. Since the printhead prints dots at 1600 dpi, each dot is approximately  $22.5\mu\text{m}$  in diameter, and spaced  $15.875\mu\text{m}$  apart. Because the printing is bi-level, the input image should be dithered or error-diffused for best results. Typically a Memjet printhead for a particular application is page-width. This enables the printhead to be stationary and allows the paper to move past the printhead. A Memjet printhead is composed of a number of identical  $1/2$  inch Memjet segments.

The printer module 10 comprises a body 11 housing the Memjet printhead. Power is supplied by a three volt battery housed in battery compartment 12. The printhead is activated to commence printing when a business card (or similar sized printable media) is inserted into slot 13. Male connector 14 and female connector 15 facilitate connection of other modules to the printer module 10.

FIG 2 shows a camera module 20. The camera module provides a point-and-shoot camera component to the compact printer system as a means of capturing images. The camera module comprises a body 21 having a female connector 22. A lens 23 directs an image to an image sensor and specialized image processing chip within the camera 24. A conventional view finder 25 is provided as well as a lens cap 26. An image is captured when the Take button 27 is pushed. Captured images are transferred to the Printer Module 10 for subsequent printing, manipulation, or storage. The Camera Module also contains a self-timer mode similar to that found on regular cameras.



FIG 3 shows a Memory Module 30 comprising a body 31, LCD 32, IN button 33, OUT button 34 and SELECT button 35. The Memory Module 30 is a standard module used for storing photographic images captured by the Camera 20. The memory module stores 48 images, each of which can be accessed either at full resolution or at thumbnail resolution. Full resolution provides read and write access to individual images, and thumbnail resolution provides read access to 16 images at once in thumbnail form.

The Memory Module 30 attaches to other modules via a female connector 36 or male connector 37. The male and female connectors allow the module to be connected at either end of a configuration. Power is provided from the Printer Module 10 via the Serial Bus.

A Communications Module 40 is shown in FIG 4. The communications module 40 consists of a connector 41 and a cable 42 that terminates in an appropriate connector for a computer port, such as a USB port, RS232 serial port or parallel port. The Communications Module 40 allows the compact printer system to be connected to a computer. When so connected, images can be transferred between the computer and the various modules of the compact printer system. The communications module allows captured images to be downloaded to the computer, and new images for printing to be uploaded into the printer module 10.

A Flash Module 50 is shown in FIG 5. The Flash Module 50 is used to generate a flash with flash cell 51 when taking photographs with the Camera Module 20. The Flash Module attaches to other modules via female connector 52 and male connector 53. It contains its own power source. The Flash Module is automatically selected by the Camera Module when required. A simple switch allows the Flash Module to be explicitly turned off to maximize battery life.

FIG 6 shows a Timer Module 60 that is used to automate the taking of multiple photos with the Camera Module 20, each photo separated by a specific time interval. The captured photos are stored in Memory Module 30. Any flash requirements are handled by the Camera Module 20, and can therefore be ignored by the Timer Module. The Timer Module 60 consists of a body 61 housing a LCD 62, START/STOP button 63 and UNITS button 64. A SELECT button 65 allows the user to select time units and the number of units are set by UNITS button 64. The Timer Module 60 includes a male connector 66 and female connector 67. The Timer Module takes its power from the Printer Module 10 via the Serial Bus.

A Laser Module 70 is shown in FIG 7. The Laser Module 70 consists of a body 71 containing a conventional laser pointer operated by button 72. As the Laser Module is a terminal module it only has one connector, which in the example is a male connector 73. The Laser Module is an isolated module, in that it does not perform any image capture, storage, or processing. It exists as a functional addition to the compact printer system. It is provided because laser pointer services are typically incorporated into other pen-like devices. The Laser Module contains its own power supply and does not appear as a device on the Serial Bus.

The Effects Module shown in FIG 8 is an image processing module. It allows a user to select a number of effects and applies them to the current image stored in the Printer Module 10. The effects include borders, clip-art, captions, warps, color changes, and painting styles. The Effects Module comprises a body 81 housing custom electronics and a LCD 82. A CHOOSE button 83 allows a user to choose between a number of different types of effects. A SELECT button 84 allows the user to select one effect from the number of effects of the chosen type. Pressing the APPLY button 85 applies the effect to image stored in the Printer Module 10. The Effects Module obtains power from the Serial Bus. Male connector 86 and female connector 87 allow the Effects Module to be connected to other compact printer system modules.

FIG 9 shows a Character Module 90 that is a special type of Effects Module (described above) that only contains character clip-art effects of a given topic or genre. Examples include The Simpsons®, Star Wars®, Batman®, and Dilbert® as well as company specific modules for McDonalds® etc. As such it is an image processing module. It consists of a body 91 housing custom electronics and a LCD 92. SELECT button 93 allows the user to choose the effect that is to be applied with APPLY button 94. The Character Module obtains power from the Serial Bus through male connector 95 and female connector 96.

The Adaptor Module 100, shown in FIG 10, is a female/female connector that allows connection between two modules that terminate in male connectors. A male/male connector (not shown) allows connection between two modules that terminate in female connectors. The Adaptor Module is a housekeeping module, in that it facilitates the use of other modules, and does not perform any specific processing of its own.

All "through" modules have a male connector at one end, and a female connector at the other end. The modules can therefore be chained together, with each module connected at either end of the chain. However some modules, such as the Laser Module 70, are terminating modules, and therefore have either a male or female connector only. Such single-connector modules can only be connected at one end of the chain. If two such modules are to be connected at the one time, an Adaptor Module 100 is required.

FIG 11 shows a Pen Module 110 which is a pen in a module form. It is an isolated module in that it attaches to the compact printer system but is completely independent of any other module. It does not consume or require any power. The Pen Module is defined because it is a convenient extension of a pen shaped, pen sized device. It may also come with a cap 111. The cap may be used to keep terminating connectors clean in the case where the chain ends with a connector rather than a terminating module.

To assist with accurately feeding a business card sized print media into slot 13 of the printer module 10, a dispenser module 120 is provided as shown in FIG12. The dispenser module 120 comprises a body 121 that holds a store of business card sized print media. A Printer Module 10 locates into socket 122 on the dispenser module 120. When correctly aligned, a card dispensed from the dispenser module by slider 123 enters slot 13 and is printed.

In the sense that a minimum configuration compact printer system must be able to print out photos, a minimum compact printer configuration contains at least a Printer Module 10. The Printer Module holds a single photographic image that can be printed out via its Memjet printer. It also contains the 3V battery required to power the compact printer system.

In this minimum configuration, the user is only able to print out photos. Each time a user inserts a business card 130 into the slot in the Printer Module, the image in the Printer Module is printed onto the card. The same image is printed each time a business card is inserted into the printer. In this minimum configuration there is no way for a user to change the image that is printed. The dispenser module 120 can be used to feed cards 130 into the Printer Module with a minimum of fuss, as shown in FIG 13.

By connecting a Camera Module 20 to the minimum configuration compact printer system the user now has an instant printing digital camera in a pen, as shown

in FIG 14. The Camera Module 20 provides the mechanism for capturing images and the Printer Module 10 provides the mechanism for printing them out. The battery in the Printer Module provides power for both the camera and the printer.

When the user presses the "Take" button 27 on the Camera Module 20, the image is captured by the camera 24 and transferred to the Printer Module 10. Each time a business card is inserted into the printer the captured image is printed out. If the user presses "Take" on the Camera Module again, the old image in the Printer Module is replaced by the new image.

If the Camera Module is subsequently detached from the compact printer system, the captured image remains in the Printer Module, and can be printed out as many times as desired. The Camera Module is simply there to capture images to be placed in the Printer Module.

FIG 15 shows a further configuration in which a Memory Module 30 is connected to the configuration of FIG 14. In the embodiment of FIG 15, the user has the ability to transfer images between the Printer Module 10 and a storage area contained in the Memory Module 30. The user selects the image number on the Memory Module, and then either sends that image to the Printer Module (replacing whatever image was already stored there), or brings the current image from the Printer Module to the specified image number in the Memory Module. The Memory Module also provides a way of sending sets of thumbnail images to the Printer Module.

Multiple Memory Modules can be included in a given system, extending the number of images that can be stored. A given Memory Module can be disconnected from one compact printer system and connected to another for subsequent image printing.

With the Camera Module 20 attached to a Memory Module/Printer Module compact printer system, as shown in FIG 15, the user can "Take" an image with the Camera Module, then transfer it to the specified image number in the Memory Module. The captured images can then be printed out in any order.

By connecting a Communications Module 40 to the minimum configuration compact printer system, the user gains the ability to transfer images between a PC and the compact printer system. FIG 16 shows the configuration of FIG 15 with the addition of a Communications Module 40. The Communications Module makes the Printer Module 10 and any Memory Modules 30 visible to an external computer system. This allows the download or uploading of images. The communications

module also allows computer control of any connected compact printer modules, such as the Camera Module 20.

In the general case, the Printer Module holds the "current" image, and the other modules function with respect to this central repository of the current image. The Printer Module is therefore the central location for image interchange in the compact printer system, and the Printer Module provides a service to other modules as specified by user interaction.

A given module may act as an image source. It therefore has the ability to transfer an image to the Printer Module. A different module may act as an image store. It therefore has the ability to read the image from the Printer Module. Some modules act as both image store and image source. These modules can both read images from and write images to the Printer Module's current image.

The standard image type has a single conceptual definition. The image definition is derived from the physical attributes of the printhead used in the Printer Module. The printhead is 2 inches wide and prints at 1600dpi in cyan, magenta and yellow bi-level dots. Consequently a printed image from the compact printer system is 3200 bi-level dots wide.

The compact printer system prints on business card sized pages (85mm x 55mm). Since the printhead is 2 inches wide, the business cards are printed such that 1 line of dots is 2 inches. 2 inches is 50.8mm, leaving a 2mm edge on a standard business-card sized page. The length of the image is derived from the same card size with a 2mm edge. Consequently the printed image length is 81mm, which equals 5100 1600dpi dots. The printed area of a page is therefore 81mm x 51mm, or 5100 x 3200 dots.

To obtain an integral contone to bi-level ratio a contone resolution of 267 ppi (pixels per inch) is chosen. This yields a contone CMY page size of 850 x 534, and a contone to bi-level ratio of 1:6 in each dimension. This ratio of 1:6 provides no perceived loss of quality since the output image is bi-level.

The printhead prints dots in cyan, magenta, and yellow ink. The final output to the printed page must therefore be in the gamut of the printhead and take the attributes of the inks into account. It would at first seem reasonable to use the CMY color space to represent images. However, the printer's CMY color space does not have a linear response. This is definitely true of pigmented inks, and partially true for dye-based inks. The individual color profile of a particular device (input and output) can vary

considerably. Image capture devices (such as digital cameras) typically work in RGB (red green blue) color space, and each sensor will have its own color response characteristics.

Consequently, to allow for accurate conversion, as well as to allow for future  
5 image sensors, inks, and printers, the CIE  $L^*a^*b^*$  color model [CIE, 1986, CIE 15.2 Colorimetry: Technical Report (2<sup>nd</sup> Edition), Commission Internationale De l'Eclairage] is used for the compact printer system.  $L^*a^*b^*$  is well defined, perceptually linear, and is a superset of other traditional color spaces (such as CMY, RGB, and HSV).

10 The Printer Module must therefore be capable of converting  $L^*a^*b^*$  images to the particular peculiarities of its CMY color space. However, since the compact printer system allows for connectivity to PCs, it is quite reasonable to also allow highly accurate color matching between screen and printer to be performed on the PC. However the printer driver or PC program must output  $L^*a^*b^*$ .

15 Each pixel of a compact printer image is therefore represented by 24 bits: 8 bits each of  $L^*$ ,  $a^*$ , and  $b^*$ . The total image size is therefore 1,361,700 bytes (850 x 534 x 3).

20 Each image processing module is able to access the image stored in the Printer Module. The access is either to read the image from the Printer Module, or to write a new image to the Printer Module.

The communications protocol for image access to the Printer Module provides a choice of internal image organization. Images can be accessed either as 850 x 534 or as 534 x 850. They can also be accessed in interleaved or planar format. When  
25 accessed as interleaved, each pixel in the image is read or written as 24 bits: 8 bits each of  $L^*$ ,  $a^*$ ,  $b^*$ . When accessed as planar, each of the color planes can be read or written independently. The entire image of  $L^*$  pixels,  $a^*$  pixels or  $b^*$  pixels can be read or written at a time.

30 In a preferred embodiment, the Camera Module includes the image processing chip which is responsible for enhancing the captured image to produce a high quality  $L^*a^*b^*$  image for transmission to the Printer Module 10.

The input image comes from an image sensor. Although a variety of image sensors are available, the Bayer color filter array (CFA) is preferred. The Bayer CFA has a number of attributes that are described here.

The image captured by the CMOS sensor (via a taking lens) is assumed to have been sufficiently filtered so as to remove any aliasing artifacts. The sensor itself has an aspect ratio of approximately 3:2, with a resolution of 850 x 534 samples to match the image resolution of the final output image. The most likely pixel arrangement is the Bayer color filter array (CFA), with each 2x2 pixel block arranged in a 2G mosaic as shown in FIG 17. Other pixel arrangements are also possible and will be suitable for certain applications. For example, a 2R mosaic will enhance the red end of the spectrum.

Each contone sample of R, G, or B (corresponding to red, green, and blue respectively) is 10-bits. Note that each pixel of the mosaic contains information about only one of R, G, or B. Estimates of the missing color information must be made before the image can be printed out.

Thus, the CFA only provides a single color component per pixel (x,y) coordinate. To produce the final image we need to have the other color component values at each pixel. With one color per pixel, we may have the red component for a particular position, but we need to estimate blue and green. Or we may have green, and need to estimate red and blue.

Resampling is one of the steps in the image enhancement process. To decide how best to resample, it is best to consider each color plane in relation to the full CFA resolution (no rotation). This is shown in FIG 18.

Looking at the red and blue planes in FIG 18, the full CFA resolution version of the color plane can be created by scaling up the number of pixels sampled from the mosaic in each dimension by 2. The intermediate pixels can be generated by means of a reconstruction filter (such as a Lanczos or Exponential filter). Only one dimension in the kernel is required, since the kernel is symmetric. Since red and blue have different offsets in terms of their initial representation within the CFA sample space, the initial positions in the kernel will be different.

The following relationship holds for red and blue mapping of output coordinates (in 534 space) to input coordinates:

$$x' = (x/ops) \quad \& \quad y' = (y/ops)$$

where  $x, y$  = coordinate in output resolution space;

$x', y'$  = coordinate in input space;

$ops = 2$  = output resolution pixels per input space sample.

The number of output resolution pixels per sample, ops, is a constant value of

2. This means that given a starting position in input space, we can generate a new line of CFA resolution pixels by adding a  $\Delta x$  and  $\Delta y$  of 1/2 and 0 respectively 533 times. The fractional part of  $x$  and  $y$  in input space can be directly used for looking up the kernel coefficients for image reconstruction and resampling. Since  $\Delta x$  is 1/2, we only require 2 sets of kernel coefficients.

Since the red and blue planes are scaled up, there will not be any aliasing artifacts introduced by the resampling process.

The green plane cannot be simply scaled up in the same way as red or blue, since each line of the green plane represents different pixels - either the odd or even pixels on alternate lines. Although in terms of the number of pixels it is representative to say the green image is 425 x 534, the image could equally be said to be 850 x 267. This confusion arises because of the checkerboard nature of the green pixels, where the distance between pixels is not equal in  $x$  and  $y$  dimensions, and does not map well to image reconstruction or resampling. The number of interpolation methods used by other systems for green plane reconstruction is testimony to this - from nearest neighbor replication to linear interpolation to bi-linear interpolation and heuristic reconstruction.

The mapping of output coordinates (in 534 space) to input coordinates is conceptually the same for green as it is for red and blue. For the green plane the following relationship holds:

$$x' = (x/ops) \quad \& \quad y' = (y/ops)$$

where  $x, y$  = coordinate in output resolution space;

$x', y'$  = coordinate in input space;

$ops = 1$  = output resolution pixels per input space sample.

Setting the number of output resolution pixels per sample,  $ops$ , to 1 allows the direct usage of coordinates in CFA resolution input space. However, once we have a coordinate in CFA resolution input space, we cannot perform image reconstruction and resampling on the samples in the same way as red or blue due to the checkerboard nature of the green plane.

Instead, for the purposes of high quality image reconstruction and resampling, we can consider the green channel to be an image rotated by 45 degrees. When we look at the pixels in this light, as shown in FIG 19, a high quality image reconstruction and resampling method becomes available.



Looking at FIG 19, the distance between the sampled pixels in the X and Y directions is now equal. The actual distance between sampled pixels is  $\sqrt{2}$ , as illustrated in FIG 20.

Thus, the solution to resampling the green channel is to perform image reconstruction and resampling in rotated space. Although the same reconstruction filter is used as for resampling red and blue, the kernel should be different. This is because the relationship between the sampling rate for green and the highest frequency in the signal is different to the relationship for the red and blue planes. In addition, the kernel should be normalized so that the  $\sqrt{2}$  distance between samples becomes 1 as far as kernel coordinates go (the un-normalized distances between resampling coordinates must still be used to determine whether aliasing will occur however). Therefore we require two transformations:

- The first is to map unrotated CFA space into rotated CFA space. This can be accomplished by multiplying each ordinate by  $1/\sqrt{2}$ , since we are rotating by 45 degrees ( $\cos 45^\circ = \sin 45^\circ = 1/\sqrt{2}$ ).
- The second is to scale the coordinates to match the normalized kernel, which can be accomplished by multiplying each ordinate by  $1/\sqrt{2}$ .

These two transformations combine to create a multiplication factor of  $1/2$ . Consequently, as we advance in unrotated CFA space x by k, we increase by  $k/2$  in kernel x, and decrease by  $k/2$  in kernel y. Similarly, as we advance in y by k, we increase by  $k/2$  in kernel x and increase by  $k/2$  in kernel y.

The relationships between these different coordinate systems can be illustrated by considering what occurs as we generate a line of output pixels from a CFA space input image. Given a starting y ordinate in CFA input space, we begin at  $x=0$ , and advance 850 times by 1, generating a new output pixel at each new location. The movement in unrotated CFA space by 1 can be decomposed into a movement in x and a movement in y in rotated CFA space. The process is shown in FIG 21.

Since  $\cos 45^\circ = \sin 45^\circ = 1/\sqrt{2}$ , movement in unrotated CFA space by 1 equates to equal movement in x and y by  $1/\sqrt{2}$  in rotated CFA space. This amount must now be scaled to match the normalized kernel. The scaling equates to another multiplication by  $1/\sqrt{2}$ . Consequently, a movement of 1 in unrotated CFA space equates to a movement of  $1/2$  in kernel x and kernel y.

Since the  $\Delta$  of  $1/2$  is less than 1, we are scaling up, and therefore aliasing will not occur for green resampling. In addition, a  $\Delta$  of  $1/2$  means that we only require 2 sets of kernel coefficients.

A reconstruction filter for the resampled red, blue and green channels is required. The exact reconstruction filter to be used will depend on a number of issues. There is always a trade off between the number of samples used in constructing the original signal, the time taken for signal reconstruction, and the quality of the resampled image. A satisfactory trade-off in this case is 5 pixel samples from the dimension being reconstructed, centered around the estimated position  $X$  i.e.  $X-2$ ,  $X-1$ ,  $X$ ,  $X+1$ ,  $X+2$ . Due to the nature of reconstructing with 5 sample points, only 4 coefficients for the entry in the convolution kernel are required.

With generalized resampling, a kernel coefficient lookup table with  $n$  entries for each color component is created. Each entry has 4 coefficients. For advancement in output space, the changes in output space are mapped to changes in input space and kernel space. The most significant bits of the fractional component in the current kernel space are used to index into the kernel coefficients table. In this case, with red, green, and blue all requiring only 2 sets of kernel coefficients each, only 2 entries in the table are required: an entry for 0, and an entry for  $1/2$ .

The apparatus for implementing the aforementioned method of the present invention can be seen in FIG 22. Address generation is not shown.

The resampling process can be seen as 3 sets of RGB generation. RGB values must effectively be produced for 3 pixel coordinates: the pixel in question, and the pixel above and below. The process of generating a single RGB value can in turn be seen as 3 processes performed in parallel: the calculation of R, G, and B, all for a given pixel coordinate. Due to the differences in resampling each channel, it is necessary to effectively run three image reconstruction filters, one on each channel of the image.

Consequently, calculation of the medium resolution R pixel is achieved by running an image reconstruction filter on the R data. Similarly, calculation of the medium resolution G and B pixels is achieved by running an image reconstruction filter on the G and B data. Although the kernels are symmetric in  $x$  and  $y$ , they are not the same for each color plane. R and B are likely to be the same kernel due to their

similar image characteristics, but the G plane, due to the rotation required for image reconstruction, must have a different kernel.

To calculate a given color plane's medium resolution pixel value, 24 cycles are available (since 72 cycles in total are available for producing the components of R, G and B). To apply the kernel to a 4x4 sample area, the 1D kernel (indexed by x) is applied to each of the 4 rows of 4 input samples. The 1D kernel (indexed by y) is then applied to the resultant 4 pixel values. The final result is the output resampled pixel. Applying a single coefficient each cycle gives a total of 16 cycles to generate the 4 intermediate values, and 4 cycles to generate the final pixel value, for a total of 20 cycles.

The input pixels are each 10 bits (8:2), and kernel coefficients are 12 bits. 14 bits of precision are kept during the 4 steps of each application of the kernel (8:6), but only 10 bits are saved for the result (8:2). Thus the same convolve engine can be used when convolving in x and y. The final output of R, G, or B is only 8 bits. The convolve unit for the resampling process is shown in FIG 23.

The process of resampling then, involves 20 cycles, as shown in Table 1. Note that the Row 1, Pixel 1 etc. refers to the input from Buffer 1, which is managed by a known addressing mechanism.

Table 1. The 20 Cycle Resample			
Cycle	Kernel	Apply Kernel to:	Store Result in
1	X[1]	Row 1, Pixel 1	TMP
2	X[2]	Row 1, Pixel 2	TMP
3	X[3]	Row 1, Pixel 3	TMP
4	X[4]	Row 1, Pixel 4	TMP, V1
5	X[1]	Row 2, Pixel 1	TMP
6	X[2]	Row 2, Pixel 2	TMP
7	X[3]	Row 2, Pixel 3	TMP
8	X[4]	Row 2, Pixel 4	TMP, V2
9	X[1]	Row 3, Pixel 1	TMP
10	X[2]	Row 3, Pixel 2	TMP
11	X[3]	Row 3, Pixel 3	TMP
12	X[4]	Row 3, Pixel 4	TMP, V3
13	X[1]	Row 4, Pixel 1	TMP
14	X[2]	Row 4, Pixel 2	TMP
15	X[3]	Row 4, Pixel 3	TMP
16	X[4]	Row 4, Pixel 4	TMP, V4
17	Y[1]	V1	TMP
18	Y[2]	V2	TMP
19	Y[3]	V3	TMP
20	Y[4]	V4	TMP (for output)

Regarding the address generation for kernel lookup, because the scaling up is by 2, the delta values are  $1/2$ . Consequently each kernel is 1 dimensional, with 2 entries in the table. The most significant bit (truncated) of the fractional component in the current kernel space is used to index into the kernel coefficients table. For the first 16 cycles, the X ordinate is used to index the kernel, while in the next 4 cycles, the Y ordinate is used. Since the kernel is symmetric, the same kernel can be used for both X and Y.

For each of the 534 resampled values, 3 pixels need to be produced - the pixel in question, and the pixels above and below that pixel. Rather than generate a center pixel and then move up and down from that center pixel, a pixel is generated and then two pixels below it are generated. The second pixel generated is taken to be the center pixel. Returning to the original row, the next 3 pixels in the next output position are then generated. In this way, 3 pixels for each of the 534 positions are generated.

Address generation for the green sub-buffer within Buffer 1 is more complicated than the red and blue sub-buffers because, to resample the green channel, we must effectively rotate the channel by 45 degrees. Furthermore, there are twice as many green pixels than red or blue pixels. Resampling means the reading of more samples in the same amount of time - there are still 16 samples read to generate each pixel, but there is a higher likelihood of advancing the buffer each time. The exact likelihood depends on the scale factor used.

In the preferred embodiment, a RAM is used as a cyclical buffer for the green channel. The green sub-buffer is a 66 entry RAM with a logical arrangement of 11 rows, each containing 6 entries.

The samples in Buffer 1 represent a checkerboard pattern in the CFA. Consequently, samples in one row (e.g. addresses 0, 11, 22, 33, 44, 55) may represent odd or even pixels, depending on the current line within the entire image. For example, for a basic 2x2 CFA cell, as shown in FIG 17, with even rows having samples at odd pixels and odd rows having samples at even pixels, the converse would be true for a rotation of the 2x2 CFA cell through 90 degrees.

Consequently, when a 4x4 sampling area is mapped onto the buffer, there are two possibilities for the interpretation of the samples. As a result, there are two types of addressing, depending on whether the current line is represented by odd or even pixels. This means that even rows with image rotation 0 will have the same

addressing as odd rows with image rotation 90 since they both hold odd pixels. Likewise, the odd rows with image rotation 0 will have the same addressing as even rows with image rotation 90 since they both hold even pixels. This means the physical CFA orientation can be taken account of.

5       The actual 4x4 sampling window is the way the buffer is effectively rotated by 45 degrees, the 45 degree rotation being necessary for effective resampling of the green channel.

10       Regarding the red and blue channels, the red and blue sub-buffers of Buffer 1 are also RAMs accessed as cyclical buffers, as for the green sub-buffer. However, each buffer is 30 bytes, but has a logical arrangement of 6 rows, each containing 6 entries.

15       The address generation mechanism for the red and blue channels is different from the green channel. However, rather than design two addressing mechanisms, it is possible to apply the green addressing scheme to the red and blue channels, and simply use different values in look up tables. This reduces design complexity.

For red and blue there is no scaling between movement in kernel space and movement in the input space. There is also no rotation.

20       The sampling process for a given 534 position line cannot begin until there are enough entries in Buffer 1, (placed there by a WhiteBalance/RangeExpansion Unit of an Image Enhancement Unit). This will occur 128 cycles after the start of each new line. Obviously, green, red and blue generation must start at the same time.

25       Throughout the specification the aim has been to describe the preferred embodiments of the invention without limiting the invention to any one embodiment or specific collection of features. Persons skilled in the relevant art may realize variations from the specific embodiments that will nonetheless fall within the scope of the invention.

CLAIMS

1. A method for up-interpolating a Bayer mosaic image from input space to output space, said Bayer mosaic image comprising a plurality of four-pixel blocks, each pixel in said blocks being one of three different colors with one of two of said pixels being a dominant color and two of said pixels being non-dominant colors, said method including the steps of:
- reading a two dimensional color plane of said Bayer image for each said color; mapping said pixels of said dominant color from said input space to said output space by:
- multiplying each ordinate of said input space by  $1/\sqrt{2}$ ; and scaling coordinates of said input space to a normalized coefficient kernel by multiplying said ordinates by  $1/\sqrt{2}$ ;
- mapping said pixels of said non-dominant colors by multiplying each ordinate of said input space by  $1/2$ ;
- for each color, convolving said input space pixels with a coefficient kernel for each color; and writing said mapped pixels to a storage location.
2. The method of claim 1 wherein said three different colors are red, green and blue.
3. The method of claim 1 or 2 wherein said dominant color is green.
4. The method of claim 1 wherein said coefficient kernel is the same for said two non-dominant colors but different for said dominant color.
5. The method of claim 1 wherein, for said dominant color, said mapping step further includes sampling a  $4 \times 4$  pixel block.
6. An apparatus for up-interpolating a Bayer mosaic image from input space to output space, said Bayer mosaic image comprising a plurality of four-pixel blocks, each pixel in said blocks being one of three different colors with one of two of said pixels being a dominant color and two of said pixels being non-dominant colors, said apparatus comprising:
- an input buffer for each color for storing said input space pixel values; a coefficient kernel for each color, said coefficient kernel for said dominant color being normalized;

a convolve unit for each color for convolving said input space pixel values with said kernel coefficients; and  
an output buffer for storing mapped pixel values.

- 5 7. The apparatus of claim 6 further comprising processing means for sampling a 4x4 pixel block for said dominant color.

8. A method of interpolating a Bayer image of red, green and blue pixels from an input space to an output space, the method including the steps of:  
receiving the Bayer image; and  
mapping each of the colors to the output space in accordance with the  
10 following equations:

$$x'=(x/ops)+k_1$$

$$y'=(y/ops)+k_2$$

- 15 where x,y is a coordinate in the output space, x'y' is the coordinate in the input space, ops is the number of pixels in the output space per input space sample, and  $k_{1,2}$  are either 0 or-0.5 depending on the color and the desired relative rotational orientation of the image.

9. The method of claim 8 wherein, for the green pixels in the input space, each ordinate of the input space is multiplied by  $1/\sqrt{2}$ .  
10. The method of claim 8 wherein, for the green pixels in the input space, each coordinate of the input space is multiplied by  $1/\sqrt{2}$ .  
20

11. A method of sampling a Bayer image having two dimensional planes of red, green and blue pixels, the method including the steps of:  
rotating the green plane by  $45^\circ$ ;  
sequentially sampling an m x m pixel block of the rotated plane, where m is an integer greater than 1;  
25 providing an address for the  $m^2$  samples by determining a starting address for a first of the samples and thereafter applying a predetermined fixed sequence of offsets to obtain the addresses of the remaining samples.

12. The method of claim 11 wherein the step of determining the starting address is responsive to the relative rotational orientation of the image.  
30

13. The method of claim 11 wherein  $m=4$  and there are sixteen offsets.

14. An apparatus for sampling a Bayer image having two dimensional planes of red, green and blue pixels, the apparatus comprising:

input means for rotating the green plane by 45°;

processing means for sequentially sampling an  $m \times m$  pixel block of the rotated plane, where  $m$  is an integer greater than 1;

address means for providing an address for the  $m^2$  samples by determining a

5

starting address for a first of the samples and thereafter applying a

predetermined fixed sequence of offsets to obtain the addresses of the remaining samples.

09575123.0523310



## ABSTRACT

A method of, and an apparatus for, image conversion. The three color channels of a Bayer mosaic image are up-interpolated from input space to output space. The pixels sampled from each two-dimensional color plane of the Bayer image are convolved with a coefficient kernel for each color. To facilitate reconstruction and resampling, the color space for a dominant pixel color of the Bayer image is effectively rotated.

The generation of each color value for a given pixel coordinate is carried out in parallel using an identical convolve unit and a dedicated coefficient kernel for each color.




FIG. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 11




FIG. 10




FIG. 12




FIG. 13




FIG. 14



8/15




FIG. 15

002250 22152560




FIG. 16




R	G
G	B

2x2 pixel block  
in sensor

R	G	R	G	R	G
G	B	G	B	G	B
R	G	R	G	R	G
G	B	G	B	G	B

Bayer mosaic of several  
2x2 pixel blocks

*FIG. 17*



$R_0$	$R_1$	$R_2$	
$R_3$	$R_4$	$R_5$	

Full CFA res red plane  
(captured pixels marked)


$B_0$	$B_1$	$B_2$	
$B_3$	$B_4$	$B_5$	

Full CFA res blue plane  
(captured pixels marked)

	$G_0$	$G_1$	$G_2$
$G_3$		$G_4$	$G_5$
	$G_6$		$G_8$
$G_9$		$G_{10}$	$G_{11}$

Full CFA res green plane  
(captured pixels marked)

FIG. 18



Full CFA res green plane  
(captured pixels marked)




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23



Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032  
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION</b> <b>(37 CFR 1.63)</b>  <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing      OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	<b>Attorney Docket Number</b>	PP17US
	<b>First Named Inventor</b>	Simon Robert Walmsley
	<b>COMPLETE IF KNOWN</b>	
	<b>Application Number</b>	/
	<b>Filing Date</b>	
	<b>Group Art Unit</b>	
	<b>Examiner Name</b>	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**METHOD AND APPARATUS OF IMAGE CONVERSION**

the specification of which

(Title of the Invention)

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY) \_\_\_\_\_ as United States Application Number or PCT International

Application Number \_\_\_\_\_ and was amended on (MM/DD/YYYY) \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
PQ0560	Australia	05/25/1999	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	
		<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.**DECLARATION — Utility or Design Patent Application**

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☐ Registered practitioner(s) name/registration number listed below

Place Customer Number Bar Code Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

 Direct all correspondence to: ☒ Customer Number or Bar Code Label

24011

OR

☐

Correspondence address below

Name	Kia Silverbrook				
Address	Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	ZIP	2041
Country	Australia	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))			Family Name or Surname		
Simon Robert			Walmsley		
Inventor's Signature	<i>Simon Walmsley</i>				Date
					May 16, 2000
Residence: City	Epping	State	NSW	Country	Australia
				Citizenship	Australian
Post Office Address	Unit 3, 9 Pembroke Street				
Post Office Address					
City	Epping	State	NSW	ZIP	2121
				Country	Australia

☒ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (3-97)  
 Approved for use through 9/30/98. OMB 0651-0032  
 Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

**DECLARATION****ADDITIONAL INVENTOR(S)  
Supplemental Sheet**Page 1 of 1

<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))				Family Name or Surname			
Paul				Lapstun			
Inventor's Signature	<i>Paul Lapstun</i>					Date	May 16, 2000
Residence: City	Rodd Point	State	NSW	Country	Australia	Citizenship	Norwegian
Post Office Address	13 Duke Avenue						
Post Office Address							
City	Rodd Point	State	NSW	ZIP	2046	Country	Australia
<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	
<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

00575122.062300